

64617 M117 75W 12V 20/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

| | |
|----------------|---------------------------------------|
| Product Number | 54124 |
| Product Name | 64617 M117 75W 12V 20/CS 1/SKU |
| Application | Projector |
| Product Remark | - p (Operating Position) = Horizontal |

Electrical data

| | |
|-----------------|------|
| Nominal Wattage | 75 W |
| Nominal Voltage | 12 V |
| Type of Current | AC |

Light technical data

| | |
|-------------------------|----------|
| Working Distance a (in) | 1.024 in |
| Working Distance a (mm) | 26 mm |
| Color Rendering Index | 100 |
| Average Rated Life | 25 h |


Physical attributes

| | |
|-----------------------------|----------------|
| Base | G5.3-4.8 BIPIN |
| Bulb Shape | MR11 |
| Maximum Overall Length (in) | 1.398 in |
| Maximum Overall Length (mm) | 35.5 mm |
| Length l (in) | 1.398 in |
| Length l (mm) | 35.5 mm |
| Length l max. (in) | 1.398 in |
| Length l max. (mm) | 35.5 mm |
| Diameter d (in) | 1.378 in |
| Diameter d (mm) | 35.00 mm |

Additional product data

| | |
|--------------------|---------|
| Operating Position | p 90/15 |
|--------------------|---------|

Product datasheet



Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54124 | 4050300231211 | Folding box (SKU) | 1 | 1.3 in x 1.3 in x 2 in | |
| 54124 | 4050300664675 | Shipping box (Case) | 20 | 7.5 in x 3.2 in x 5.2 in | 1 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.