

Maxi SharXS HTI 2000W/D10/60 10/CS 1/SKU



Product features and benefits

- MAXI SHARXS lamp family provides consistent lengths and bases for simplified fixture designs
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54328		
Product Name	Maxi SharXS HTI 2000W/D10/60 10/CS 1/SKU		
Family Brand Name	SharXS HTI		
Product Remark	 Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius. Base has notch for pre-alignment. Lamp bases need to be forced cooled. 		

Electrical data

Nominal Wattage	2000 W	
Nominal Voltage	105 V	
Current (A)	19 A	

Light technical data

Luminous Flux	200000 lm		
Light Center Length - LCL (in)	3.54 in		
Light Center Length - LCL (mm)	90 mm		
Color Temperature	6500 K		
Average Rated Life	750 h		

Physical attributes

Base	SFC15,5		
Maximum Overall Length (in)	8.66 in		
Maximum Overall Length (mm)	220 mm		
Length I (mm)	220 mm		
Length l1 (in)	8.66 in		
Length l1 (mm)	220 mm		
Diameter d (in)	1.102 in		
Diameter d (mm)	28.00 mm		
Distance a (in)	3.540 in		
Distance a (mm)	90 mm		
Electrode Gap - cold (mm)	10 mm		

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	450 C

Product datasheet

Forced Cooling	Forced Cooling Required	
Hot Restart	Yes	

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54328	4008321334947	Shipping box (Case)	1	4.5 in x 3.2 in x 12 in	0.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.