

HTI 250 W/32C 2/CS 1/SKU



Product features and benefits

- Robust design with precision reflector alignment
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54089
Product Name	HTI 250 W/32C 2/CS 1/SKU
Family Brand Name	HTI
Application	Entertainment and Effect Lighting, Fiber Optic
Product Remark	- p (Operating Position) = Horizontal

Electrical data

Nominal Wattage	250 W
Nominal Voltage	45 V
Current (A)	6 A
Type of Current	AC

Light technical data

Working Distance a (mm)	32 mm
Color Temperature	5600 K
Color Rendering Index	70
Average Rated Life	250 h


Physical attributes

Base	LEADS WITH AMP 350809-1 CONNEC
Bulb Shape	REFLECTOR
Maximum Overall Length (mm)	73 mm
Length l (mm)	73 mm
Length l max. (mm)	73 mm
Diameter d (in)	2.638 in
Diameter d (mm)	67.00 mm
Electrode Gap - cold (mm)	2.5 mm

Additional product data

Operating Position	P 20
Maximum Base Temperature (°C)	230 C
Cooling	Forced
Hot Restart	Yes

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54089	4050300021805	Folding box (SKU)	1	3.4 in x 3.4 in x 4.1 in	0.3 lb
54089	4050300248820	Shipping box (Case)	2	7.3 in x 3.8 in x 4.5 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.