

EGT 1000W 120V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54664
Product Name	EGT 1000W 120V 12/CS 1/SKU
General Description	1,000 watt, tungsten halogen, medium to high voltage, single-ended
Application	Stage & Studio
LIF Code	CP/40
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	27500 lm
Light Center Length - LCL (in)	2.477 in
Light Center Length - LCL (mm)	63.5 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	250 h

Physical attributes

Base	G22 Medium Bipost
Bulb Shape	T6
Maximum Overall Length (in)	5.460 in
Maximum Overall Length (mm)	140 mm
Length l (in)	5.460 in
Length l (mm)	140 mm
Length l max. (in)	5.460 in
Length l max. (mm)	140 mm
Diameter d (in)	0.945 in
Diameter d (mm)	24.00 mm
Distance a (in)	2.477 in
Distance a (mm)	63.5 mm
Filament	C-13D
Filament Dimensions Length (in)	0.7220 in

Product datasheet

Filament Dimensions Length (mm)	18.5 mm
Filament Dimensions Width (in)	0.624 in
Filament Dimensions Width (mm)	16 mm

Additional product data

Operating Position	s 90
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54664	4062172147057	Folding box (SKU)	1	2.2 in x 2.2 in x 7.5 in	0.3 lb
54664	4062172147064	Shipping box (Case)	12	9.8 in x 7.4 in x 8.5 in	3.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.