

## HPL 575W 115V/X 12/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

## Technical data

### General product information

|                   |                             |
|-------------------|-----------------------------|
| Product Number    | 54807                       |
| Product Name      | HPL 575W 115V/X 12/CS 1/SKU |
| Family Brand Name | HPL                         |
| Application       | Stage & Studio              |

### Electrical data

|                 |       |
|-----------------|-------|
| Nominal Wattage | 575 W |
| Nominal Voltage | 115 V |
| Type of Current | AC    |

### Light technical data

|                                |          |
|--------------------------------|----------|
| Luminous Flux                  | 12360 lm |
| Light Center Length - LCL (in) | 2.352 in |
| Light Center Length - LCL (mm) | 60.3 mm  |
| Color Temperature              | 3065 K   |
| Color Rendering Index          | 100      |
| Average Rated Life             | 2000 h   |

### Physical attributes

|                             |              |
|-----------------------------|--------------|
| Base                        | G9.5 W/HSINK |
| Bulb Shape                  | T19          |
| Maximum Overall Length (in) | 4.1 in       |
| Maximum Overall Length (mm) | 104 mm       |
| Length l (in)               | 4.1 in       |
| Length l (mm)               | 104 mm       |
| Length l max. (in)          | 4.1 in       |
| Length l max. (mm)          | 104 mm       |
| Diameter d (in)             | 0.741 in     |
| Diameter d (mm)             | 19.00 mm     |
| Distance a (in)             | 2.352 in     |
| Distance a (mm)             | 60.3 mm      |
| Filament                    | 4-C8         |

### Additional product data

|                    |     |
|--------------------|-----|
| Operating Position | Any |
|--------------------|-----|

## Product datasheet

---

### Packaging Information

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54807          | 4062172147316 | Folding box (SKU)   | 1        | 1.6 in x 1.6 in x 5.1 in     | 0.2 lb       |
| 54807          | 4062172147323 | Shipping box (Case) | 12       | 7 in x 5.4 in x 6 in         | 1.8 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.