
HP 375W 115V GLG 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54520
Product Name	HP 375W 115V GLG 12/CS 1/SKU

Electrical data

Nominal Wattage	375 W
Nominal Voltage	115 V
Type of Current	AC

Light technical data

Luminous Flux	10000 lm
Light Center Length - LCL (in)	2.38 in
Light Center Length - LCL (mm)	60.45 mm
Color Temperature	3250 K
Color Rendering Index	100
Average Rated Life	300 h

Physical attributes

Base	G9.5 MEDIUM BIPIN
Bulb Shape	T6
Length l (in)	4 in
Length l (mm)	101.6 mm
Diameter d (in)	0.750 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.380 in
Distance a (mm)	60.45 mm
Filament	C-13D

Additional product data

Lamp Type	SINGLE END
-----------	------------

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54520	4008321501561	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.1 lb
54520	4008321501578	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.