
DWE PAR36 MFL 120V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54500
Product Name	DWE PAR36 MFL 120V 12/CS 1/SKU
Application	STAGE & STUDIO

Electrical data

Nominal Wattage	650 W
Nominal Voltage	120 V

Light technical data

Luminous Flux	24000 lm
Beam Type	MFL
Centerbeam Candlepower (cp)	24000 cp
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	100 h

Physical attributes

Base	SCREW TERMINAL G53
Bulb Shape	PAR36
Length l (in)	2.559 in
Length l (mm)	65 mm
Diameter d (in)	4.500 in
Diameter d (mm)	114.30 mm

Additional product data

Operating Position	ANY
Lamp Type	PAR36

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54500	4008321228505	Folding box (SKU)	1	3.7 in x 3.7 in x 4 in	0.7 lb
54500	4008321228512	Shipping box (Case)	12	12.2 in x 8.4 in x 8.5 in	6.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.