
ENH-5 250W 125V 24/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54988
Product Name	ENH-5 250W 125V 24/CS 1/SKU
Application	Projector - Overhead
Product Remark	<ul style="list-style-type: none">- s (Operating Position) = Vertical, base down- Lumens refers to screen lumens.

Electrical data

Nominal Wattage	250 W
Nominal Voltage	125 V
Type of Current	AC

Light technical data

Luminous Flux	340 lm
Working Distance a (in)	5.948 in
Working Distance a (mm)	152.5 mm
Color Temperature	3150 K
Color Rendering Index	100
Average Rated Life	175 h

Physical attributes

Base	GY5.3 BIPIN
Bulb Shape	T3.5
Maximum Overall Length (in)	1.735 in
Maximum Overall Length (mm)	44.5 mm
Length l (in)	1.735 in
Length l (mm)	44.5 mm
Length l max. (in)	1.735 in
Length l max. (mm)	44.5 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm

Additional product data

Operating Position	s 90
Lamp Type	MR16

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54988	0046135549885	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54988	10046135549882	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.