

6.6A 64337 IRC-A 48-30 20/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield lighting

Product datasheet

Technical data

General product information

Product Number	59070
Product Name	6.6A 64337 IRC-A 48-30 20/CS 1/SKU
Application	Airfield/Airport

Electrical data

Nominal Wattage	48 W
Current (A)	6.6 A

Light technical data

Luminous Intensity (cd)	23000 cd
Color Rendering Index	100
Average Rated Life	3000 h

Physical attributes

Base	LEADS W/FEMALE FLAT CONNECTORS
Bulb Shape	MR16
Maximum Overall Length (in)	1.772 in
Maximum Overall Length (mm)	45 mm
Diameter d (in)	1.984 in
Diameter d (mm)	50.40 mm

Additional product data

Lamp Type	SINGLE ENDED
-----------	--------------

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
59070	4008321341174	Folding box (SKU)	1		
59070	10046135590709	Shipping box (Case)	20	10.1 in x 4.3 in x 5.2 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.