

## 6.6A/200T5/CL/64380 25/CS 1/SKU



### Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

### Areas of application

- Airfield lighting

## Product datasheet

### Technical data

#### General product information

Product Number	58707
Product Name	6.6A/200T5/CL/64380 25/CS 1/SKU
Application	Airfield/Airport
LIF Code	J1/40

#### Electrical data

Nominal Wattage	200 W
Current (A)	6.6 A
Type of Current	AC

#### Light technical data

Luminous Flux	4400 lm
Color Rendering Index	100
Average Rated Life	1000 h

#### Physical attributes

Bulb Shape	R111
Maximum Overall Length (in)	2.583 in
Maximum Overall Length (mm)	65.6 mm
Diameter d (in)	0.591 in
Diameter d (mm)	15.00 mm
Filament	CC-8
Filament Dimensions Length (in)	0.1170 in
Filament Dimensions Length (mm)	3 mm
Filament Dimensions Width (in)	0.39 in
Filament Dimensions Width (mm)	10 mm

#### Additional product data

Operating Position	Any
Lamp Type	SINGLE ENDED

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58707	0046135587078	Folding box (SKU)	1	1.3 in x 1.3 in x 4.4 in	
58707	4008321282415	Shipping box (Case)	25	6.7 in x 6.7 in x 4.5 in	1.1 lb

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.