

XBO 4000W/HPN 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Projection
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	69060
Product Name	XBO 4000W/HPN 1/CS 1/SKU
Family Brand Name	XBO
General Description	4000 Watt Xenon High Pressure Digital Cinema NEC Projection Lamp
Application	Digital Cinema Projection
Product Remark	<ul style="list-style-type: none">- OFR=Ozone Free- s (Operating Position) = Vertical, base down- p (Operating Position) = Horizontal- This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.

Electrical data

Nominal Wattage	4000 W
Nominal Voltage	34 V
Current (A)	120 A
Current Control Range (A)	90-125 A
Type of Current	DC

Light technical data

Luminous Flux	190000 lm
Light Center Length - LCL (in)	5.67 in
Light Center Length - LCL (mm)	144 mm
Average Rated Life	650 h
Warranty Hours (hr)	650 hrs
Service Warranty Lifetime (hr)	750 hrs

Physical attributes

Base Anode	SFaX27-9.5
Base Cathode	SFa27-20
Bulb Shape	T60
Maximum Overall Length (mm)	345 mm
Length l1 max. (in)	13.58 in
Length l1 max. (mm)	345 mm
Diameter d (in)	2.165 in
Diameter d (mm)	55.00 mm

Product datasheet

Distance a (in)	5.670 in
Distance a (mm)	144 mm
Electrode Gap - cold (mm)	5 mm

Additional product data

Operating Position	s15 p15
Maximum Base Temperature (°C)	230 C
Cooling	Required

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69060	4062172030267	Shipping box (Case)	1	19.7 in x 8 in x 8 in	3.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.