

## XBO 4500W/HPN L 1/CS 1/SKU



### Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

### Areas of application

- Digital Projection
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

## Product datasheet

### Technical data

#### General product information

Product Number	69051
Product Name	XBO 4500W/HPN L 1/CS 1/SKU
Application	Digital Cinema Projection
Product Remark	<ul style="list-style-type: none"><li>- OFR=Ozone Free</li><li>- s (Operating Position) = Vertical, base down</li><li>- p (Operating Position) = Horizontal</li><li>- This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.</li></ul>

#### Electrical data

Nominal Wattage	4500 W
Nominal Voltage	30 V
Current (A)	150 A
Current Control Range (A)	108-150 A
Type of Current	DC

#### Light technical data

Light Center Length - LCL (mm)	171.5 mm
Average Rated Life	1300 h
Warranty Hours (hr)	1300 hrs
Service Warranty Lifetime (hr)	1500 hrs

#### Physical attributes

Base Anode	SFaX30-9.5
Base Cathode	SFa30-20
Bulb Shape	T60
Maximum Overall Length (mm)	428 mm
Electrode Gap - cold (mm)	5.8 mm

#### Additional product data

Operating Position	s15 p15
Maximum Base Temperature (°C)	230 C
Cooling	Required

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69051	4052899343351	Shipping box (Case)	1	26.4 in x 12.2 in x 12.2 in	6.3 lb
69051	4062172030595	Shipping box (Case)	1	23.2 in x 9.2 in x 9.2 in	4.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.