

XBO 4000W/HS XL 1/CS 1/SKU



Product features and benefits

- High luminance (point source)
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart
- Long lamp life with eXtreme Life technology

Areas of application

- Digital
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	69474			
Product Name	XBO 4000W/HS XL 1/CS 1/SKU			
Application	Cinema Film Projection			
Product Remark	 S=Short OFR=Ozone Free s (Operating Position) = Vertical, base down p (Operating Position) = Horizontal This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. XL=Xtreme Life Lamp base(s) with M 5x0.9 thread. 			

Electrical data

Nominal Wattage	4000 W
Nominal Voltage	30 V
Current (A)	135 A
Current Control Range (A)	80-150 A
Type of Current	DC

Light technical data

Light Center Length - LCL (mm)	171 mm		
Average Rated Life	1500 h		
Warranty Hours (hr)	1500 hrs		

Physical attributes

Base Anode	SFaX30-9.5
Base Cathode	SFa30-7.9
Bulb Shape	K0156
Maximum Overall Length (mm)	410 mm
Length l1 max. (mm)	410 mm
Diameter d (in)	2.756 in
Diameter d (mm)	70.00 mm
Distance a (mm)	171 mm
Electrode Gap - cold (mm)	7 mm

Additional product data

Product datasheet

Maximum Base Temperature (°C)	230 C
Cooling	Required

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69474	4008321412812	Shipping box (Case)	1	23.2 in x 9.2 in x 9 in	4.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.