

HPL 750/120/X 12/CS 1/SKU



Product features and benefits

- Ultra compact filament design (UCF) for high lumen output
- Unique top bridgeless construction improves beam uniformity for lamps with ≤ 120 volts
- Unique gas fill which improves light output and minimizes risk of arc-out
- Special heat sink base for maximum durability in high temperature applications
- Reinforced pinch seal for extra mechanical strength
- Foam packaging for easier handling and installation
- Optimum system performance with TP22H socket

Areas of application

- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54653
Product Name	HPL 750/120/X 12/CS 1/SKU
Family Brand Name	HPL
Application	Stage & Studio

Electrical data

Nominal Wattage	750 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	16400 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3065 K
Color Rendering Index	100
Average Rated Life	2000 h

Physical attributes

Base	G9.5 W/HSINK
Bulb Shape	T19
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	4-C8

Additional product data

Operating Position	Any
--------------------	-----

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54653	4052899347946	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54653	4052899347953	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.