Product family datasheet

OSRAM

TYREseal ESSENTIAL






Made to OE specification Direct replacement for the cars original tyre sealant



No tools required No need to remove the valve core



Quick repair solution Be on the road within 10 minutes





The OSRAM TYREseal ESSENTIAL tyre sealant is a direct replacement for the car's original tyre sealant.Made to OE specification using the latest particle gel technology, the OSRAM tyre sealant will repair punctures up to 6mm and can then be driven on for up to 200km, so you are able to complete your journey or get a replacement tyre form a service centre.With no tools or jacks required, the process of repairing a punctured tyre is quick and easy and will get you back on the road within 10mins. The sealant is designed to flow through valves so it is safe to use with TMPS valves. No need to remove valve cores. The bottle is a universal design, so it can be stored with the car makers sealant kit and is compatible with OSRAM tyre inflators and most other inflators.Once the tyre is off, the sealant can be washed out easily to allow for a permanent repair if desired. The solution is non-toxic, so when it is rinsed out, it is environmentally friendly

Product family datasheet

Technical data

	General Product Information	Physical Attributes & Dimensions		
Product description	Global order reference	Height	Width	Length
TYRE seal ESSENTIAL	OTS4502ESN	190.0 mm	90.0 mm	90.0 mm
	Colors & materials	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Material	Declaration no. in SCIP database		
TYRE seal ESSENTIAL	Liquid	In work		

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.