## **OSRAM**

# LEDriving HL INTENSE NXT H4



Up to +400% more brightness 1)

More light<sup>1)</sup> allows to see farther and therefore react sooner. Obstacles and hazards can be recognized sooner on race tracks.Compared to minimum ECE R112



**CANbus free** 

Prevents error messages in board computers during failure detection



## Compact LED replacement for conventional H4 high and low beam lamps

Easy installation thanks to a wide range of suitable OSRAM accessories



5-year OSRAM guarantee

For precise conditions, please refer to www.osram.com/amguarantee



#### OSRAM's highest performing off-road LED retrofit lamp ever!

With up to +400% more brightness1) and integrated CANbus (for avoiding error messages on the dashboard2) the OSRAM LEDriving HL INTENSE NXT ensures a compact LED replacement of conventional H4 high and low beam lamps. These LED retrofit lamps are 12V compatible, come with an optimized beam pattern, color temperature of 6,000 K and thanks to the wide range of suitable OSRAM accessories the installation is easy. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to traditional halogen bulbs). The pair of lamps comes with a 5-year OSRAM guarantee3).

- 1) compared to minimum ECE R112
- 2) applicable to plenty of car models 3For precise guarantee conditions please refer to www.osram.com/am-guarantee.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

## Technical data

	Product information			General Prod Information			ata
Product description	Product type (off- road vs. on-road)	• • •	on (Category uct specific)	Global order reference		Power input	Nominal voltage
LEDriving HL INTENSE NXT ≜ H4	Off-road ≜ Mainly used for Low H4 Beam, High Beam		64193DWIN	N	40.0 W/ 12.0 V 42.0 W		
				Photometric [	ata		Physical Attributes & Dimensions
Product description	Nominal wattage		Test voltage	flux		Luminous flux tolerance	Diameter
LEDriving HL INTENSE NXT ≜ H4	40.0 W/ 42.0 W 13		13.2 V	2500/3500 lm		±25 %	15.5 mm
	Lifetime	Capabilities		nental & Regulatory Information ion according Art. 33 of EU Regulation (EC) 1907/2006			
	Data	Capabilities		-	•		(EC) 1907/2006
Product description		Technology	Informati	on according A	•	J Regulation	(EC) 1907/2006  Declaration no. in SCIP database

## Product family datasheet

### Download Data

#### File



User instruction

LEDriving HL INTENSE NXT H4 64193DWINN



User instruction

GPRS\_Safety symbols instructions

## **Application advice**

For more detailed application information and graphics please see product datasheet.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





