

# TYREinflate Connect 650



### Download via App

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



### Auto Stop function

Auto Stop function when pre-set pressure is reached.



### Leak Detection

Including function to detect a loss of tyre pressure



### OSRAMconnect

Connecting you with your car



### OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation<sup>3)</sup> of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and their associated information, has active reminder functions and a leak detection function. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes<sup>2)</sup> gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product<sup>1)</sup>1) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)2) Based on inflating a 13" tyre from flat to 2.41 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

## Данные о продуктовой линейке

### Technical data


Описание продукта	General Product Information	Электрические параметры	Physical Attributes & Dimensions	
	Номер заказа	Номинальное напряжение	Высота	Ширина
TYRE inflate Connect 650	OTIC650	11.1 V	219.0 mm	90.0 mm

Описание продукта	Длина	Температуры и условия управления	Дополнительные данные	Возможности / мощности
		Уровень шума (дБ)	Тип дисплея	Предохранитель
TYRE inflate Connect 650	200.0 mm	90 dB	Digital	10 A

Описание продукта	Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Основной идентификатор изделия	Список компонентов вещества 1	CAS-номер вещества 1	Инструкция по безопасному использованию
TYRE inflate Connect 650	4052899622883	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Описание продукта	Номер декларации в базе данных SCIP
TYRE inflate Connect 650	f2f01f10-b494-4e57-ad3c-e7f344875985

### Загрузка данных

Файл	
	User instruction TYREinflate Connect 650

#### Советы по безопасности

Достигает максимального уровня шума 90 дБ.

#### Соответствие стандартам

- 1) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)
- 2) Based on inflating a 13" tyre from flat to 2.41 BAR
- 3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres  
Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.

#### Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

#### Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.