

TYREinflate Connect 650



Download via App

The smart app stores the tyre pressure for your car and downloads it to the OSRAM TYREinflate Connect 650



Auto Stop function

Auto Stop function when pre-set pressure is reached.



Leak Detection

Including function to detect a loss of tyre pressure



OSRAMconnect

Connecting you with your car



OSRAMconnect App compatible tyre inflator

Improve your driving performance and fuel costs by making sure your tyre pressure is correct. The OSRAM TYREinflate Connect 650 is a digital tyre inflator compatible with the OSRAMconnect app, with a backlit display for easy and accurate pressure measurement and inflation³⁾ of tyres, showing pressure values in BAR, kPA and PSI. The app can store up to 5 vehicles and their associated information, has active reminder functions and a leak detection function. Furthermore, the OSRAM TYREinflate Connect 650 has an automatic switch-off function as soon as the preset pressure is reached. In addition, it has a storage compartment for valve caps, a 3.3 m long retractable power cable with a 12V fuse plug, a 65 cm long flexible air hose with an easily accessible holder and an additional LED light for illumination at night or in poor lighting conditions and a large on/off switch for additional manual operation. An inflation time of about 3 minutes²⁾ gets you on the road and where you need to be fast. Also included is a 3-piece adapter set, for bikes, balls and other inflatables, and a durable storage bag. OSRAM provides a 2-year guarantee on this product¹⁾1) For precise conditions please refer to: www.osram.com/am-guarantee2) Based on inflating a 13" tyre from flat to 2.41 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Данные о продуктовой линейке

Technical data

	Электрические параметры	Размеры и вес			Дополнительные данные	Возможности / мощности
Описание продукта	Номинальное напряжение	Высота	Ширина	Длина	Тип дисплея	Предохранитель
TYRE inflate Connect 650	11.1 В	219.0 mm	90.0 mm	200.0 mm	Digital	10 A

	Классификация	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Описание продукта	Номер заказа	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
TYRE inflate Connect 650	OTIC650	28-06-2024	4052899622883	In work

Загрузка данных

Файл	
	User instruction TYREinflate Connect 650

Советы по безопасности
Достигает максимального уровня шума 90 дБ.

Соответствие стандартам
1) OSRAM LIGHTsignal HAL BEACON LIGHT одобрены в соответствии с правилами ECE, могут устанавливаться и эксплуатироваться на дорогах общего пользования. Помимо одобрения продукта ECE, необходимо соблюдать особые требования и законодательство стран. Обратите внимание: использование вращающихся маячков регулируется специфическими правилами, установленными законодательством дорожного движения конкретной страны. 2) Больше информации доступно по ссылке: www.osram.com/am-guarantee

Рекомендации по использованию: Более детальная информация об использовании и изображения находятся в техническом паспорте и в руководстве пользователя.

Рекомендации по применению
Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание
В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.