

TYREinflate 4000

TYREinflate 4000 OTIR4000



Inflation Time

Inflate the tyre to the desired pressure in approximately 3,5 minutes 1)2)



Deflator Valve

For deflating too much air



Digital Auto Stop

Automatic stop function when the preset pressure is reached



Cordless and rechargeable

Can be used with or without direct power supply



Rechargeable Digital Tyre Inflator

The OSRAM TYREinflate 4000 is a cordless and rechargeable tyre inflator with Li-Ion battery, making it an ideal companion for camping and road trips. The OTIR 4000 digital tyre inflator can inflate a tyre in just 3,5 minutes1)2). The auto stop function and the deflator valve help to keep the tyres optimally inflated. The backlit LED display and integrated LED light provide improved readability of the pressure settings and improved illumination of the working area even in reduced visibility conditions or at night. Memory setting means you can store pressures for up to 4 vehicles.OSRAM offers a 2-year guarantee1) on this product.1) For precise conditions please refer to: www.osram.com/am-guarantee2) Based on inflating a 13" tyre from flat to 2.4 BAR3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres

Product family datasheet

Technical data

| Product description | Product information | | | |
|---------------------|---------------------|-----------|-----------------|-----------|
| | Deflation valve | LED Light | Preset Function | Auto stop |
| TYRE inflate 4000 | Yes | Yes | Yes | Yes |

| Product description | Storage Case | General Product Information | Physical Attributes & Dimensions | |
|---------------------|--------------|-----------------------------|----------------------------------|---------|
| | | Global order reference | Length | Width |
| TYRE inflate 4000 | Yes | OTIR4000 | 61.0 mm | 95.0 mm |



| Product description | Height | Colors & materials | Operating Conditions | Additional product data |
|---------------------|--------|--------------------|----------------------|-------------------------|
| | | Material | Noise Level (dB) | Display Type |
| TYRE inflate 4000 | 150 mm | Plastic | 90 dB | Digital |

| Product description | Extras | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---------------------|---|--------------|--|-------------------------------|
| | | Fuse | Date of declaration | Candidate list substance 1 |
| TYRE inflate 4000 | Air hose, USB C charging cable, 12 V D.C cable, 3 inflator adaptors, storage case | 15 A | 22-09-2024 | Lead |

| Product description | CAS No. of substance 1 | Safe use instruction | Declaration no. in SCIP database |
|---------------------|------------------------|--|--------------------------------------|
| TYRE inflate 4000 | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 593dbda7-6369-474c-8925-958ce33490fe |

Product family datasheet

Download Data

| File | |
|---|--|
|  | User instruction TYREinflate 4000 |
|  | Movie application TYREinflate 4000 Product Video (EN) |

Legal advice

1) For precise conditions please refer to: www.osram.com/am-guarantee

2) Based on inflating a 13" tyre from flat to 2.41 BAR

3) Measurements of the tyre pressure and inflation of the tyres to the optimum tyre pressure must always be conducted on cold tyres
Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.